Product Data Sheet

FONDO K Plus

Water-based pigmented acrylic-siloxane primer coat

DESCRIPTION

Opaque intermediate base coat for external thermal insulation system specifically designed for subsequent application of thick coloured coatings. The PLUS technology ensures that the film is resistant to algae, mould and microorganisms.
For professional users only.

MAIN PROPERTIES

- High coverage;
- Protects the film from mold formation;
- Specific for TERMOK8 systems

TECHNICAL DATA

Film aspect EN 13300	Matt (≤ 10 gloss 85°)
Thickness EN 13300	Class B, medium (100 > 300 µm)
Classification (UNI 8681 / UNI 8682)	One-pack, physical drying, matt, acrylic base coat paint dispersed in water. (B3.CO.A.2.FA)
Specific weight	1430 ± 50 g/l
	7-8
Type of binder	Acrylic
Solid content	70 ± 2%
Drying time	Can be overpainted after 6 hrs, completely dry after 12 hrs
	Cat A/c: limit 40 g/l (2010); this product contains a maximum of 34 g/l of VOCs

CHARACTERISTICS

Coverage	With the application of 1 coat: 6 - 7 m2/l
Coverage per pack	(14 l): 84 m2, approx. Coverage varies according to substrate absorption.
Overpaintable	Compatibility with other products: compatible with all water-based products
Colour range	White and Colours can be produced
Diluted with	Water
	10-20%=100-200 ml per litre of product

APPLICATION

Notes:
Suitable Substrates:
Cement-based renders, lime-based plaster, painted plaster, exposed reinforced concrete features, precast concrete features and fibre cement
Ambient Conditions:
min +5°C max +35°C max RH 80%

Product Data Sheet

Preparation of the Substrate:

All substrates must be free of release agents and must be dry, clean and coherent. Renders must be sufficiently cured according to the type of material and manufacturer's instructions. In the case of old paint or dusty substrates, we recommend applying a coat of PRIMACRIL consolidating primer or removing them if this is not sufficient.

Type of Equipment:

brush, short-haired roller, spraying equipment.

Application Procedure:

Dilute FONDO K PLUS as indicated and mix with a low speed mixer. Apply one coat and cross the direction of brush strokes during application.

STORAGE

Disposal and safety indications:

Dispose of in accordance with local regulations.
For information on possible hazards, refer to the safety data sheet

Packaging: 14 litres

Storage:

1 year when stored in undamaged packages at between 5 and 30°C; cannot endure frost and direct sunlight